

INTEX

**GAME
MAARI
CHHE!**
GUJARAT NI BAARI CHHE!



CATALOGUE

IT PRODUCTS 2016

WWW.INTEXUAE.COM

WWW.THEGUJARATLIONS.COM

INTEX Technologies ,started in Dubai in year 2002 is a major business participant in the consumer electronics , mobility and IT accessories. A well-known player in over 66 countries, Intex has put itself on the map as a world class brand of quality consumer products.

INTEX Technologies is an ISO 9001:2008 certified company by virtue of its quality products at affordable price point and excellent after sales service support with which over a period of time INTEX has built credibility and achieved trust across its vast network of channel partners and millions of satisfied end customers. Intex Technologies is well known for its consistent policy of transparent win win situation and ethical trade practices.

Today INTEX Technologies has its global presence across the South East Asia, GCC & Middle East, Africa, some parts Latin America & Europe and CIS countries. Considering the advancement of technology, INTEX expanded its product verticals by adding Smart Phones, Tablet PC's, Mobile Accessories in addition to IT accessories, Speakers, Home theatre systems, Power Products, Networking & PC Cables . These Segments exhibit an exhaustive portfolio of 30 product groups comprising 300+ SKUs of INTEX.

INTEX not only enjoys the reputation of being the 3rd largest selling brand in India but also having good market share across the globe. Our aim is to position INTEX as most accepted and admired brand in modern world of technology. INTEX incepted as a brand in India, now has expanded to Australia, China, Hong Kong, UAE, and plans to explore its operations in Russia and other countries in coming years.

INTEX is proud to have experienced technical department which contributes to bring quality products, SKUs in the market through our state-of-the-art manufacturing facilities in India & China. Intex's manufacturing domain comprises of three associate manufacturing units (belonging to the Group) located at Jammu, India (30,000 sq.ft. & 20,000 sq. ft built-up area) and Manpura (Baddi, HP) India (51,000 sq. ft). The units have been producing multimedia speakers, Mobile Phone batteries, chargers and have also produced UPS, Home UPS, Notebooks and DVD players in the past. The company intends to vertically integrate backwards into manufacturing of more products incorporating foreign technology from global leaders. In addition to these units, Intex gets products contract manufactured from carefully selected vendors in China and India.

The company has a strong Centre for Design and Development in India which is well-equipped with modern facilities and is headed by highly qualified engineers looking after product development, product and component specifications, benchmarking, quality up-gradation, technology development and scanning, etc. This activity ensures that state-of-the-art products are offered as per the latest global standards.

INTEX 2.0 Ch TOWER SPEAKERS

IT-11500 SUF BT 2.0 Channel Tower Speaker with Cordless MIC & Bluetooth



Specifications

Power Output (R.M.S.)	42W + 42W
Power Supply	AC 220V ~ 240V / 50Hz - 60Hz
Speaker Unit / Size	20.32cm(8")x2 + 10.16cm(4")x2 + 5.08cm(2")x2
Impedance	4 Ω
Frequency Response	45Hz ~ 20KHz
S/N Ratio	≥ 60dB
Separation	≥ 40dB
Bass up/down	±15dB
Sensitivity	< 500mV
Input & Output Jack	RCA Jack Input / Clamp Output
FM Frequency Receiver	88MHz to 108MHz
LED Display	Yes
Power Indicator LED	Yes
MP3 Playability with USB/SD/MMC	Yes
AUX Audio Input Compatible	Yes
Bluetooth	Yes
Controls Provided	Rotary Type (Vol, Bass, Treble, Mic Vol, Echo), Mode, EQ, Mute, Next/Vol+, Play/Pause, Prev/Vol-
MIC	Cordless MIC Function & Wire MIC
MIC Playability with Volume & Echo Control	Yes
Karaoke Support	Yes

IT-12800 SUF BT 2.0 Channel Tower Speaker with Cordless MIC & Bluetooth



INTEX 5.1 Ch HOME THEATRE

IT-4100 SUF BT

5.1 Channel Home Theatre Pro-logic Output
From 2.0 Channel Subwoofer Input with Bluetooth



Specifications

Power Output (R.M.S.)	20W + 5Wx5
Power Supply	AC 220V ~ 240V / 50Hz - 60Hz
Speaker Unit / Size	Main Unit : 10.2cm (4")/20W Satellite : 7.62cm (3")/5Wx5
Impedance	4 Ω
Frequency Response	Main Unit : 40Hz ~ 200Hz Satellite : 160Hz ~ 20KHz
S/N Ratio	≥60dB
Separation	≥ 45dB
Bass up/down	±15dB
Sensitivity	500mV rms @ 1KHz
Input & Output Jack	RCA Jack
FM Frequency Receiver	88MHz to 108MHz
LED Display	Yes
MP3 Playability with USB/SD/MMC	Yes
AUX Audio Input Compatible	Yes
Bluetooth Accessibility / Version	Yes / V2.1+EDR
Max. Transmit Power	Class 2, 40 dBm (at antenna pad)
Bluetooth Data Rates	Upto 3Mbps(over the air)
Frequency	2.402GHz-2.480GHz
Power Sensitivity	Better than-80 dBm
Range	10 Meters
Controls Provided	MODE, VOL-/PREV, PLAY/PAUSE, VOL+/NEXT



INTEX TROLLEY SPEAKERS

IT-TSF28 BT

2.1 Trolley Speaker
with 2 Wireless MIC & Bluetooth



Specifications

Output Power	60W
Speaker Size	12"
Impedance	4Ω
Frequency Response	40Hz-20KHz
S/N Ratio	>=60db
Separation	>=40db
BT version	EDR+V2.1
FM Frequency	87.5-107.9MHz
Mic Frequency	262.85MHz-268.85MHz
Power Supply	AC 220V-240V/50Hz-60Hz
Input&Output Jack	RCA Jack
N.W	11.21KG
G.W	13.21KG



IT-TSF29 BT

2.1 Trolley Speaker
with 2 Wireless MIC & Bluetooth



Specifications

Output Power	120W
Speaker Size	12"
Impedance	4Ω
Frequency Response	40Hz-20KHz
S/N Ratio	>=60db
Separation	>=40db
BT version	EDR+V2.1
FM Frequency	262.85MHz to 268.85MHz
Power Supply	AC 220V-240V/50Hz-60Hz
Input&Output Jack	RCA Jack
N.W	13.9 KG
G.W	15.7KG

INTEX TROLLEY SPEAKERS

IT-TSP6015BT

2.1 Trolley Speaker
with Wireless MIC & Bluetooth



Specifications

Woofer	15woofer,120magnetic,4 Ohm
Tweeter/Driver	4 inches,80magnetic,6 Ohm
Output pwr	100 W
FM Radio	YES
Antenna (Telescope/Internal)	YES
LED/LCD display	LED
Remote Controller	YES
USB/SD slot	YES
Wheels	YES
Handles	YES
Plastic/wooden/MDF	Plastic
6.35mm phone jack	YES
2RCA	YES
Speak On	YES
Microphone	YES
Wireless Microphone	2pc
Audio cable 3.5/2RCA	YES
AC Power Dual Voltage	220V
UL AC Power cord, length	2m 1.5m
Bluetooth	YES



IT-TSP2312BT

2.1 Trolley Speaker
with 2 Wireless MIC & Bluetooth



Specifications

Woofer	12woofer,100magnetic,4 Ohm
Tweeter/Driver	Piezoelectric soprano
Output pwr	250 Wrms 45W
FM Radio	YES
Antenna (Telescopic/Internal)	YES
LED/LCD display	LED
Remote Controller	YES
USB/SD slot	YES
Wheels	YES
Handles	YES
Plastic/wooden/MDF	Plastic (Black)
6.35mm phone jack	YES
2RCA	YES
Wireless Microphone	2pc
Audio cable 3.5/2RCA	220V
AC Power Dual Voltage	220V
UL AC Power cord, length	2m 1.5m
Bluetooth	YES
Disco Light/ Laser Lights	YES



INTEX DJ SPEAKERS

IT - DJ 420K

2.0 Channel DJ Speaker with
2 Cordless MIC & Bluetooth
& Karaoke Support



Specifications

Power Output (R.M.S.)	60W + 60W
Power Supply	AC 220V ~ 240V / 50Hz - 60Hz
Speaker Unit / Size	Main Unit : 25.4cm(10")x4 Tweeter : 7.62cm(3")x6
Impedance	4 Ω
Frequency Response	50Hz ~ 20KHz
S/N Ratio	≥ 60dB
Separation	≥ 40dB
Bass up/down	±15dB
Sensitivity	< 550mV
Input & Output Jack	RCA Jack Input / Clamp Output
FM Frequency Receiver	88MHz to 108MHz
Power Indicator LED	Yes
MP3 Playability with USB/SD/MMC	Yes
AUX Audio Input Compatible	Yes
Bluetooth Accessibility / Version	Yes / V2.1
Max. Transmit Power	Class 2, 40 dBm (at antenna pad)
Bluetooth Data Rates	Upto 3Mbps(over the air)
Frequency	2.402GHz-2.480GHz
Power Sensitivity	Better than-80 dBm
Range	10 Meters
UART Data Transfer Rate	15200bps
Controls Provided	Rotary Type (Vol, Bass, Treble, Mic Vol, Echo), Input, Next/Tuner+ Play/Pause/ Scan, Prev/Tuner- Double Cordless MIC Function & Wire MIC
MIC	Yes
MIC Playability with Volume & Echo Karaoke Support	Yes

IT - DJ 215K

2.0 Channel DJ Speaker with
2 Cordless MIC & Bluetooth
& Karaoke Support



INTEX DJ SPEAKERS

IT - DJ 220K

2.0 Channel DJ Speaker with
Cordless MIC & Bluetooth
& Karaoke Support



Specifications

Power Output (R.M.S.)	60W + 60W
Power Supply	AC 220V ~ 240V / 50Hz - 60Hz
Speaker Unit / Size	Main Unit : 25.4cm(10")x4 Tweeter : 7.62cm(3")x6
Impedance	4 Ω
Frequency Response	50Hz ~ 20KHz
S/N Ratio	≥ 60dB
Separation	≥ 40dB
Bass up/down	±15dB
Sensitivity	< 550mV
Input & Output Jack	RCA Jack Input / Clamp Output
FM Frequency Receiver	88MHz to 108MHz
Power Indicator LED	Yes
MP3 Playability with USB/SD/MMC	Yes
AUX Audio Input Compatible	Yes
Bluetooth Accessibility / Version	Yes / V2.1
Max. Transmit Power	Class 2, 40 dBm (at antenna pad)
Bluetooth Data Rates	Upto 3Mbps(over the air)
Frequency	2.402GHz-2.480GHz
Power Sensitivity	Better than-80 dBm
Range	10 Meters
UART Data Transfer Rate	15200bps
Controls Provided	Rotary Type (Vol, Bass, Treble, Mic Vol, Echo), Input, Next/Tuner+ Play/Pause/ Scan, Prev/Tuner- Single Cordless MIC Function & Wire MIC
MIC	Yes
MIC Playability with Volume & Echo Karaoke Support	Yes

INTEX DJ SPEAKERS

IT - DJ 600

2.0 Channel DJ Speaker with MIC & Karaoke Support



Specifications

Power Output (R.M.S.)
Power Supply
Speaker Unit / Size

30W + 30W
AC 220V ~ 50Hz
Main Unit : 20.32cm (8")x2,
Tweeter : (3.5")x2

Impedance
Frequency Response
S/N Ratio
Separation
Bass up/down
Sensitivity
Input & Output Jack
FM Frequency Receiver
Power Indicator LED
MP3 Playability with USB/SD/MMC
AUX Audio Input Compatible
Controls Provided

4 Ω
45Hz ~ 20KHz
≥60dB
±15dB
< 500mV
RCA Jack
88MHz to 108MHz
Yes
Yes
Yes
Rotary Type (Vol, Bass, Treble,
Mic Vol, Echo), IN Mode, Prev/
Vol-, Next/Vol+, Play/Pause
Single Wire MIC
Yes
Yes

MIC
MIC Playability with Volume & Echo
Karaoke Support

IT - DJ 601 BT

2.0 Channel DJ Speaker with MIC, Bluetooth & Karaoke Support



INTEX SUBWOOFER

IT-1875 SUF BT

2.1 Channel Subwoofer Speaker with Bluetooth



Specifications

Power Output (R.M.S.)
Power Supply
Speaker Unit / Size

12W + 3Wx2
AC 220V ~ 240V / 50Hz - 60Hz
Main Unit : 10.16cm (4") / 20W
Satellite : 7.62cm (3") / 10Wx2

Impedance
Frequency Response

Main unit : 6Ω, Satellite : 4Ω
Main Unit : 40Hz ~ 200Hz
Satellite : 200Hz ~ 20KHz

S/N Ratio
Separation
Bass up/down
Sensitivity
Input & Output Jack
FM Frequency Receiver
LED Display
Power Indicator LED
MP3 Playability with USB/SD/MMC
AUX Audio Input Compatible
Bluetooth Accessibility / Version
Max. Transmit Power
Bluetooth Data Rates
Frequency
Power Sensitivity
Range
Controls Provided

≥60dB
≥40dB
±15dB
500mV rms @ 1KHz
RCA Jack
88MHz to 108MHz
Yes
Yes
Yes
Yes / V2.1+EDR
Class 2, 40 dBm (at antenna pad)
Upto 3Mbps(over the air)
2.402GHz-2.480GHz
Better than-80 dBm
10 Meters
Rotary Type (Bass & Treble),
St-By, Eq, Mode, Prev/Vol-,
Next/Vol+, Play/Pause

IT-2590 SUF BT

2.1 Channel Subwoofer Speaker with Bluetooth



Specifications

Power Output (R.M.S.)
Power Supply
Speaker Unit / Size

20W + 10Wx2
AC 220V ~ 240V / 50Hz - 60Hz
Main Unit : 13.34cm (5.25")/20W
Satellite : 7.62cm (3")/10Wx2

Impedance
Frequency Response

4 Ω
Main Unit : 20Hz ~ 200Hz
Satellite : 200Hz ~ 20KHz

S/N Ratio
Separation
Bass up/down
Sensitivity
Input & Output Jack
FM Frequency Receiver
LED Display
MP3 Playability with USB/SD/MMC
AUX Audio Input Compatible
Controls Provided

≥60dB
≥40dB
±15dB
500mV rms @ 1KHz
RCA Jack
88MHz to 108MHz
Yes
Yes
Yes
Encoder, Mode, CH-/Previous/Vol-
CH+/Next/Vol+, Scan/Play/Pause

INTEX SUBWOOFER

IT-225SUF BT

2.1 Channel Subwoofer Speaker
with Bluetooth



Specifications

Speaker type	2.1Ch
RMS output	20W + 10W*2
Subwoofer size and Impedance	4"
Speaker size and impedance	3"
Frequency response subwoofer	40Hz-20KHz
Frequency response satellites	20Hz-20KHz
S/N Ratio	≥60dB
Separation	≥40dB
Power supply	220V-240V/50Hz-60Hz
Input	RCA Jack
USB Support	Yes
SD card support	Yes
FM radio	Yes
Remote control	Yes

IT-303SUF BT

2.1 Channel Subwoofer Speaker
with Bluetooth



Specifications

Output Power	5W+2.5W*2
Satellite speaker size	2.5"*2(4OHM5W)
Woofer speaker size	4"*1(4OHM10W)
Function	AUX+U/SD+ROMER/FM/BT
Input sensitivity	500MV
degree of separation	≥40dB
signal-to-noise ratio	≥60dB
Frequency response	Subwoofer:40-200HZ Satellite:20-18khz
Power line length	1.2M
Body size	L155*W180*H130mm
Satellite size	L90*W80*H90mm

INTEX SUBWOOFER

IT-1800 SUF

2.1 Channel Subwoofer Speaker



Specifications

Power Output (R.M.S.)	15W + 5Wx2
Power Supply	AC 220V ~ 240V / 50Hz - 60Hz
Speaker Unit / Size	Main Unit : 10.16cm (4")/15W Satellite : 7.62cm (3")/5Wx2
Impedance	Main unit : 6Ω , Satellite : 4Ω
Frequency Response	Main Unit : 20Hz ~ 200Hz Satellite : 200Hz ~ 20KHz
S/N Ratio	≥60dB
Separation	≥40dB
Bass up/down	±15dB
Sensitivity	500mV rms @ 1KHz
Input & Output Jack	RCA Jacks
FM Frequency Receiver	88MHz to 108MHz
Power Indicator LED	Yes
MP3 Playability with USB/SD/MMC	Yes
AUX Audio Input Compatible	Yes
Controls Provided	Rotary Type (Volume, Bass, Treble), Mode, Vol-/Previous/CH-, Vol+/Next/CH+, Mute/PP/FM Auto

IT-1600 SUF

2.1 Channel Subwoofer Speaker



Specifications

Power Output (R.M.S.)	15W + 5Wx2
Power Supply	AC 220V ~ 240V / 50Hz - 60Hz
Speaker Unit / Size	Main Unit : 10.16cm (4")/15W Satellite : 7.62cm (3")/5Wx2
Impedance	Main unit : 6Ω , Satellite : 4Ω
Frequency Response	Main Unit : 20Hz ~ 200Hz Satellite : 200Hz ~ 20KHz
S/N Ratio	≥60dB
Separation	≥40dB
Bass up/down	±15dB
Sensitivity	500mV rms @ 1KHz
Input & Output Jack	RCA Jack
FM Frequency Receiver	88MHz to 108MHz
Power Indicator LED	Yes
MP3 Playability with USB/SD/MMC	Yes
AUX Audio Input Compatible	Yes
Controls Provided	Rotary Type (Volume, Bass, Treble), Mode, Vol-/Previous/CH-, Vol+/Next/CH+, Mute/PP/FM Auto

INTEX SUBWOOFER

IT-2616 SUF BT

2.1 Channel Subwoofer Speaker
with Bluetooth



Specifications

Speaker Size	Main Unit : 5.25" Satellite: 3"
Max Output power	30W+10W*2
Frequency Response	Main Unit : 20Hz - 200Hz, Satellite : 200Hz -20KHz;
FM Frequency Receiver	88MHz to 108 MHz
Subwoofer Size	156*275*280mm
Satellite Size	98*160*95mm
Input & Output Jack	RCA Jack
Power Supply	AC 220V ~ 240V/50Hz
Drivers	5.25" woofer, 3" full range
Controls Provided	Volume Control, Mode, Prev/CH-/Vol-, Next/CH+/Vol+, Play/Pause/Scan

INTEX SUBWOOFER

IT-900 AC

2.1 Channel Subwoofer Speaker



Specifications

Speaker type	2.1Ch
RMS output	10W + 3W*2
Subwoofer size and Impedance	4"
Speaker size and impedance	3"
Frequency response subwoofer	40Hz-20KHz
Frequency response satellites	20Hz-20KHz
S/N Ratio	≥75dB
Separation	≥45dB
Power supply	220V-240V/50Hz-60Hz
Input	RCA Jack
USB Support	Yes
SD card support	Yes
FM radio	Yes
Remote control	Yes

IT-2617 SUF BT

2.1 Channel Subwoofer Speaker
with Bluetooth



Specifications

Speaker Size	Main Unit : 5.25" Satellite: 3"
Max Output power	30W+10W*2
Frequency Response	Main Unit : 20Hz - 200Hz, Satellite : 200Hz -20KHz;
FM Frequency Receiver	88MHz to 108 MHz
Subwoofer Size	156*275*280mm
Satellite Size	98*180*95mm
Input & Output Jack	RCA Jack
Power Supply	AC 220V ~ 240V/50Hz
Drivers	5.25" woofer, 3" full range
Controls Provided	Volume Control, Mode, Prev/CH-/Vol-, Next/CH+/Vol+, Play/Pause/Scan

IT-2615 SUF BT

2.1 Channel Subwoofer Speaker
with Bluetooth



Specifications

Speaker type	2.1Ch
RMS output	20W + 8W*2
Subwoofer size and Impedance	4"
Speaker size and impedance	3"
Frequency response subwoofer	40Hz-20KHz
Frequency response satellites	20Hz-20KHz
S/N Ratio	≥60dB
Separation	≥40dB
Power supply	220V-240V/50Hz-60Hz
Input	RCA Jack
USB Support	Yes
SD card support	Yes
FM radio	Yes
Remote control	Yes

INTEX BLUETOOTH HEADPHONES

IT-HSBT65S Wireless Stereo Joggers Headphones



Features:

Bluetooth profiles supported: Headset, Handfree
 Operation Range: Up to 10 Meters
 Music formats: MP3, WMA, AMR, FLAC, APE, Vorbis etc
 Built-in rechargeable (lithium-Polymer) battery
 Recharge time: 5 hours full charge
 Playing time: 4-6 hours
 Built-in Microphone
 Support Micro TF card input slot up to 16GB
 HD lossless decoding: Special support APE, FLAC the HD lossless file decoding, restore sound is essentially
 Signal to noise ratio: ≥ 90 DB
 Output Power: 45mW/Frequency output: 20Hz-200kHz;

Specifications

Power Supply	(BL-5B) 800mAh/3.7V
S/N Ratio	> 80dB
Power Consumption	0.25W
Earphone Output power	10mW x 2
	3.7V- 4.2V
Standrad Operating Voltage DC	Earphone Output power 10mW x 2
Battery Output Current	<100mAh
Battery Working Time	> 4 Hrs
Battery Charging Time	3 Hrs
Earphone Socket	3.5mm
Headphone(Receiver)	Wireless
Bluetooth Version	Version 3.0
Max. transmit power	< 4dBm
Power Sensitivity	< -83dBm
Range	10 Meters
Data Rates	8Kbps - 320Kbps
Frequency Response	20Hz-20KHz
Output impedance	32 E
Available color	Black
Net Weight	306 gram

INTEX BLUETOOTH SPORTS HEADSET

IT-HSBTQY7 Wireless Stereo Sports Earphone



Specifications

Description: Speaker	$\Phi 10$ mm Dynamic type
Technical standard	The AIROHA chip support Bluetooth 4.1
Transmission distance	10Meter
Holding time	8 Hours
Stand-by time	8 Hours
Charging time	About 2Hours

Bluetooth Earphone Feature :

- Exquisite fashion, fashion design.
- Support HFP1.6, A2DP1.2 and AVRCP1.4
- Supported formats: aptx (nondestructive), AAC - LC, MP3 and SBC
- Super save electricity, use special charging management,
- Better protect lithium battery low
- Anti-interference and secrecy
- Hang up and redial, refused to call, mute function, built-in bluetooth is preferred

The AIROHA chip, the magic sound shape version 4.1 support A2DP stereo
 Selling Points : The sounds is very good. The designing is very popular, When u do sport, it is very easy to bring and easy to control.

INTEX POWER BANKS

IT-PB10K Penguin Blue 10000 mAh



Specifications

Fashionable Texture Design
Capacity: 10000mAh
Battery type: Li-polymer
Input: 5V 2A(Max)
Output: 5V 1A(Max) & 5V 2.1A(Max)
Life Cycle: > 500 times
Charging time: 5-6h

IT-PB80K XL 8000 mAh



Specifications

Input: 5V/2, 1A(Max)
Output: 5V/1A(Max) & 5V/2.1A(Max)
Capacity: 8000mAh
Life Cycle: > 500 Times
Plug & Play: Yes
Built-in Battery: Yes

INTEX POWER BANKS

IT-PB10 10000 mAh



Specifications

Capacity	10000mAh
INPUT	5V/1A
OUTPUT	5V/1A
DC Output Current	0.5A-1A
Life Cycle	>500 Times
Charge Time	5 hours
Over Charge Protection	4.25V
Battery Protection	Yes
Support Mobile	Yes
Plug & Play	Yes
High Capacity	Yes
Full Compatible	Yes
Torch availability	Yes
High Security	Yes